

INSTRUCTIONS FOR INSTALLATION AND MAINTENANCE

BVP / BVP Max



CONTENTS		page
1.	SAFETY MEASURES	1
2.	USE	1
3.	STARTING THE PUMP	2
4.	RECOMMENDATIONS	2
5.	TROUBLESHOOTING	3
6.	DISPOSAL	4
7.	GUARANTEE	4

1. SAFETY MEASURES

Before starting the pump, read this instruction booklet carefully and keep it in a safe place for future reference.



For safety reasons, the pump must not be used by anyone who has not read these instructions. The pump must not be used by anyone under 16 years of age or by anyone who has not read and understood the present instruction booklet. Keep children well away from the pump when in operation..



The power cord or floating switch must never be used to carry or move the pump. Always use the pump's handle.



When handling the pump, while it is connected to the electric power supply, you should avoid all contact with water.



Never remove the plug by pulling on the power cord.



Before taking any action on the pump, always remove the plug from the power socket.



There should be no individuals present in the liquid that is being pumped while the pump is in use.



If the power supply cord has been damaged, it must be replaced by the manufacturer or his authorized customer support service in order to avoid all risks.



The pump is equipped with a thermal overload safety device. In the event of any overheating of the motor, this device automatically switches off the pump. The cooling time is roughly 15 to 20 minutes, then the pump automatically comes on again. If the overload cutout is tripped, it is essential to identify and deal with the cause of the overheating. See Troubleshooting.

2. USE

Powerful submersible pumps for draining and emptying, and for small-scale irrigation needs; they can be used with dirty water containing particles in suspension up to a maximum dimension of 2'.



The temperature of the fluid being pumped must never exceed 95°F



The pump must not be used to pump salt water, sewage, flammable, corrosive or explosive liquids (e.g. petroleum oil, petrol, and thinners), grease, oils or foodstuffs.



Comply with the rules and regulations of the local water authority when using the pump for the supply of domestic water.

3. STARTING THE PUMP



Given the different provisions applicable to the safety of electric systems in different countries, make sure that the pump system, as concerns its intended use, is in accordance with current legislation.



Before starting the pump, make sure that:

- The voltage and frequency specified on the pump's nameplate coincide with those of the available power supply;
- there are no signs of damage to the pump or its power cord;
- The electric connection is made in a dry place, protected against any risk of flooding;
- The electric system is complete with a residual current circuit-breaker GFI Ground fault Indicator (30 mA) and an efficient earthing connection;
- Any extension cords must comply with requirements of the DIN VDE Standard 0620.

Automatic operation:

The floating switch starts and stops the pump automatically. The water level that prompts the starting and stopping of the pump can be adjusted by changing the length of cable between the holder and the float.

NB The length of cable for the float must never be shorter than ½”.

Manual operation:

- a) The floating switch must be lifted in order to start pumps with a float.
- b) For pumps without a float, insert the plug.

4. RECOMMENDATIONS

To ensure the proper operation of the pump, it is important to comply with the following recommendations:



The pump must never be allowed to run dry.



Never leave the pump in operation when the delivery pipe is clogged.



The pump must be positioned so that the holes on the suction side cannot be partially or totally clogged by dirt.

- The pump must only be used when it is immersed in water. If the water runs out, the pump must be stopped immediately by removing the plug from the power supply.
- Pay careful attention when the pump is operated in manual mode.
- The pump must be placed in a stable position inside a trap or in the lowest part of the place where it is installed.
- The float must be able to move freely while the pump is in operation, so the recommended dimensions for the trap are 1”½ x1”½ .
- It is absolutely essential to prevent any risk of the pump freezing. In the event of freezing temperatures, remove the pump from the liquid, empty it and keep it in a place where it cannot freeze.

5. TROUBLESHOOTING



Before taking any troubleshooting action, disconnect the pump from the power supply. If there is any damage to the power cord or pump, any necessary repairs or replacements must be handled by the manufacturer or his authorized customer support service, or by an equally-qualified party, In order to prevent all risks.

FAULT	CAUSE	SOLUTION
The motor does not start or makes no noise	A. Make sure the motor is powered. B. The pump is not enabled by the float.	A. Check if power is supplied to the socket and that the plug is correctly inserted B. - Make sure the float can move freely. - Increase the depth of the trap.
The pump delivers no water	A. The suction grid or piping are clogged. B. The impeller is worn or stuck. C. The required head is too high for the characteristics of the pump.	A. Remove the obstruction. B. Replace the impeller or remove the obstruction.
The pump does not stop.	A. The pump is not disabled by the float.	A. Make sure the float can move freely.
The flow rate is too low	A. Make sure the suction grid is not partially clogged. B. Make sure the impeller or delivery pipe are not partially clogged or fouled.	A. Remove any obstructions. B. Remove any obstructions.
The pump stops after a brief period of operation.	A. The thermal cutout stops the pump.	A. - Make sure the fluid being pumped is not too dense, causing the motor to overheat. - Make sure the temperature of the water is not too high. - Make sure there is no solid body obstructing the impeller.

ELECTRICAL DATA

Model	P1 Watt	P1 Hp	Max Flow GPM	Voltage Volt	Frequency Hz	Head Max Ft
BVP Manual	1000	3/4	88	115	60	36
BVP Automatic	1000	3/4	88	115	60	36
BVP MAX Manual	1100	1	111	115	60	39

6. DISPOSAL

This product or its parts must be disposed of in accordance with the laws regarding the environment; Use the local, public or private, refuse collection services.

7. GUARANTEE

Any material or manufacturing defects will be corrected during the guarantee period established by current law in the country where the product is purchased. It is up to the manufacturer to decide whether to repair or replace any faulty parts.

The manufacturers guarantee covers all substantial defects attributable to manufacturing or material defects, providing the product has been used correctly and in compliance with the instructions.

The guarantee becomes null and void in the event of the following:

- unauthorized attempts to repair the appliance;
- unauthorized technical changes to the appliance;
- use of non-original spare parts;
- mishandling;
- inappropriate use. e.g. for industrial purposes.

The guarantee does not cover:

- parts liable to rapid wear and tear.

For any action under guarantee, contact an authorized customer support service, presenting your receipt for the purchase of the product.

The manufacturer accepts no liability for any inaccuracies in the present booklet due to printing or copying errors. The manufacturer reserves the right to make any changes to the product he deems necessary or useful, without affecting its essential features.

LEADER[®]
PUMPS



PUMPS AMERICA INC.
3226 BENCHMARK DRIVE
LADSON, SC 29456 USA

TEL: 1-843-824-6332
FAX: 1-843-797-3366