

www.dabpumps.com





UTILITY PUMPS ECOSUB ECOVORT

DAB PUMPS LTD.

Unit 4, Stortford Hall Industrial Park Dunmow Road, Bishops Stortford, Herts CM23 5GZ - UK

info.uk&eire@dwtgroup.com Tel.: +44 1279 652 776 Fax: +44 1279 657 727

DAB PUMPS B.V.

Brusselstraat 150 B-1702 Groot-Bijgaarden - Belgium info.belgium@dwtgroup.com Tel.: +32 2 4668353

Fax: +32 2 4669218

DAB PUMPS INC.

3226 Benchmark Drive Ladson, SC 29456 USA info.usa@dwtgroup.com Ph. : 1-843-797-5002 Fax : 1-843-797-3366

DWT GROUP Russia

100 bldg. 3 Dmitrovskoe highway, 127247 Moscow - Russia info.russia@dwtgroup.com Tel.: +7 495 739 52 50 Fax: +7 495 485-3618

DAB PUMPS B.V.

Albert Einsteinweg, 4 5151 DL Drunen - Nederland info.netherlands@dwtgroup.com Tel.: +31 416 387280 Fax: +31 416 387299

DAB PUMPEN DEUTSCHLAND GmbH

Tackweg 11 D - 47918 Tönisvorst - Germany info.germany@dwtgroup.com Tel.: +49 2151 82136-0 Fax: +49 2151 82136-36

DAB PUMPS IBERICA S.L.

Parque Empresarial San Fernando
Edificio Italia Planta 1ª
28830 - San Fernando De Henares - Madrid
Spain
info.spain@dwtgroup.com

Ph.: +34 91 6569545 Fax: +34 91 6569676

DAB PUMPS CHINA

Shandong Sheng Qingdao Shi Jinji Jishu Kaifaqu Kaituo Rd ZIP PC266510 CN - China

info.china@dwtgroup.com Tel.: +8613608963089 Fax: +8653286812210



DAB Pumps Inc.

3226 Benchmark Drive Ladson SC 29456 Phone 843-797-5002 - Fax 843-797-3366





HYDRAULIC DATA





Multi Purpose Pumps for Pound fountains & Water Falls

Multi-purpose submersible pumps for drainage, emptying, pumping water between containers, to circulate water in garden ponds, create water falls and play water features.

Suitable to pump clear water containing particles with maximum diameter up to 1/2" for the ECOSUB and 1"1/4 for the ECOVORT.

- * Drainage
- * Emptying sumps
- * Transfering water between large containers
- * Circulating water in Garden ponds
- * Water falls
- * Fountains



ECOSUB

ECOVORT

TECHNICAL DATA

CONSTRUCTION

- Anti-corrosive and rust-proof materials
- Motor with thermic overload protection
- Wear resistant shaft and impeller
- Excellent cooling of the motor that enables the pump to operate even when it is partially submerged
- Automatic version with start/ stop float switch and Manual version
- Supplied with power cable with plug and self-sealing fitting

TECHNICAL DATA


FEATURES & BENEFITS

- Plug & Play
- Large range to cover various requirements
- Provides Excellent flows"In a compact design"
- Efficient motors
- 115v 60Hz

2

- CSA and UL approved
- Dry Run protection (with Float Switch)
- Built in thermic overload

TECHNICAL DATA												
Model	HP	Watts	Volts	Frequency	Amps	Min suction	Max Flow	Max Head	Max Solids	Connection size		
ECOSUB 400	1/4	220	115	60 Hz	2.0		29 gpm	20 ft				
ECOSUB 410 & 410A	1/3	300	115	60 Hz	3.0	1/2 "	37 gpm	23 ft	1/2"	1" 1/4		
ECOSUB 420 & 420A	1/2	750	115	60 Hz	7.1		66 gpm	30 ft				
ECOVORT 510 & 510A	1/3	330	115	60 Hz	3.0	1"1/4	34 gpm	15 ft	1" 1/4	1" 1/4		
ECOVORT 520 & 520A	1/2	650	115	60 Hz	6.5	1" 1/4	60 gpm	28 ft				



							DIMENSIONS
Model	Lenght	Depth	Height	Weight	Pallet Qty		
ECOSUB 400	5.5"	5.5"	10.5"	8 lbs			
ECOSUB 410	5.5"	5.5"	10.5"	8.5 lbs			
ECOSUB 420	5.5"	5.5"	11.9"	11.5 lbs	72 + 48		
ECOVORT 510	5.5"	5.5"	11.8"	8.5 lbs			
ECOVORT 520	5.5"	5.5"	11.8"	12 lbs		lxdxh	lxdxh

3